



अखिल भारतीय आयुर्विज्ञान संस्थान , बिलासपुर
हिमाचल प्रदेश -१७४००१
All India Institute of Medical Sciences, Bilaspur
Himachal Pradesh-174001
<https://aiimsbilaspur.edu.in>
engineering@aiimsbilaspur.edu.in



AIIMS-BLS-H-09/EE-C/2026-27/506

Dated: 09/07/2026

NOTICE INVITING QUOTATION

Sealed item rate quotations as per schedule attached are hereby invited by the Local Purchase Committee on behalf of the Executive Director, AIIMS Bilaspur (HP) so as to reach in this office on or before **16/07/2026 up to 03:00 PM** and shall be opened on the same day at **03:30 pm** in the O/o Executive Engineer, AIIMS Bilaspur (HP) in the presence of intending vendors or their authorized representatives.

Name of work: Setting up of Addiction Treatment Facility (ATF) OPD only at AIIMS,Bilaspur.

-----As Per Schedule Attached-----

Terms & Conditions: -

1. The work will be carried out as per CPWD General Specifications for Civil Works amended up to date & as per the instructions of the Engineer-in-charge.
2. The work is to be completed within 60 days from issue of work order.
3. Any damages done during execution of the work/repairs are to be made good by the agency and nothing extra will be paid separately for the same.
4. The Prices quoted should be inclusive of all taxes including GST and nothing extra is to be paid.
5. The price should be inclusive of F.O.R
6. All the applicable taxes shall be deducted from the bill.
7. Compensation of delay work will be @0.5% per week.
8. GST Registration Certificate should also be attached with NIQ.
9. Enlistment Certificate with CPWD, MES, Railways, State PWD, PSU's etc.

Sd/-

Executive Engineer
AIIMS Bilaspur H.P.

Copy To: -

- (i) Institute Website
- (ii) Notice Board

Schedule of Quantity					
Setting up of addiction treatment facility (ATF) OPD only at AIIMS,Bilaspur.					
Sr. NO.	DESCRIPTION	Quantity	UNIT	Rate/unit(in Rs.) (Infigures)	Total Amount (IN RS.)
1	Providing and fixing 17 mm thick Melamine Faced Chipboard (MFC) conforming to approved quality, pre-laminated on both sides with decorative finish, having anti-bacterial and anti-fungal properties, including all necessary cutting, machining, fitting and fixing complete as per approved design and direction of Engineer-in-Charge. Exposed edges to be finished with 0.8 mm thick PVC edge band tape using hot press edge banding process complete in all respects.	44.25	sqm		
2	Providing and fixing 17 mm thick Melamine Faced Chipboard (MFC) conforming to approved quality, pre-laminated on both sides with decorative finish, having anti-bacterial and anti-fungal properties, including all necessary cutting, machining, fitting and fixing complete as per approved design and direction of Engineer-in-Charge. Exposed edges to be finished with 0.8 mm thick PVC edge band tape using hot press edge banding process complete in all respects.	22.25	sqm		
3	Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / panelling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, paneling and dash fasteners to be paid for separately) :				
	For fixed portion				
	Powder coated aluminium (minimum thickness of powder coating 50 micron)				
		23.00	kg		
4	For shutters of doors, windows & ventilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required including the cost of EPDM rubber / neoprene gasket required (Fittings shall be paid for separately)				
	Powder coated aluminium (minimum thickness of powder coating 50 micron)				
		15.00	kg		
5	Providing and fixing carbon steel galvanised (minimum coating 5 micron) dash fastener of 10 mm dia double threaded 6.8 grade (yield strength 480 N/mm ²), counter sunk head, comprising of 10 mm dia polyamide PA 6 grade sleeve, including drilling of hole in frame , concrete/ masonry, etc. as per direction of Engineer-in-charge.				
	10 x 120 mm	20.00	each		
6	Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with EPDM rubber / neoprene gasket etc. complete as per the architectural drawings and the directions of engineer-in-charge .				
	With float glass panes of 5 mm thickness (weight not less				
		3.00	sqm		
7	Providing and fixing 12 mm thick prelaminated particle board flat pressed three layer or graded wood particle board conforming to IS: 12823 Grade I Type II, in panelling fixed in aluminum doors, windows shutters and partition frames with C.P. brass / stainless steel screws etc. complete as per architectural drawings and directions of engineer-in-charge				
	Pre-laminated particle board with decorative lamination on both sides	3.00	sqm		
8	Providing and fixing aluminium tower bolts, ISI marked, anodised (anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour or shade, with necessary screws etc. complete :				
	150x10 mm	10.00	Each		
9	Providing and fixing Brass 100mm mortice latch and lock with 6 levers without pair of handles (best make of approved quality) for aluminium doors including necessary cutting and making good etc. complete.				
		1.00	Each		
10	Providing and fixing stainless steel soft closing heavy type telescopic drawer channels of approved make 500 mm long with screws etc. complete as per direction of Engineer- in-charge.				
		2.00	one set		
11	Providing and fixing bright /matt finished Stainless Steel handles of approved quality & make with necessary screws etc all complete				
	125mm	18.00	each		
12	Providing and fixing stainless steel soft closing spring hinges at 0 degree hinges (hydraulic type) of approved make/brand to cupboard shutters with full threaded steel screws including making necessary recess in board and finished etc. complete as per direction of Engineer-in-				
		20.00	each		
13	Providing and fixing aluminium extruded section body tubular type universal hydraulic door closer (having brand logo with SI, IS : 3564, embossed on the body, door weight upto 36 kg to 80 kg and door widthfrom 701 mm to 1000 mm), with double speed adjustment with necessary accessories and screws etc. complete.				

		2.00	each		
14	Providing and fixing 2 mm thick 16 to 19 mm wide PVC edge binding tape of approved quality for cupboard/wardrobe shutters including necessary synthetic resin hot pressed to edges on binding machine etc. complete as per direction of Engineer- in-charge.				
		50.00	mtr		
15	Fully Perforated Gypsum Plaster Board of size 1200 x 2400x12.5 mm having approx. 15 % perforated area with perforation size and pattern as approved by the Engineer in-charge and as per manufacturer's specification, with all 4 sides tapered and backed by acoustical tissue with NRC value not less than 0.60				
		15.00	sqm		
16	Providing and fixing special quality chromium plated brass cupboard locks with six levers of approved quality including necessary screws etc. complete.				
	Size 75 mm				
		12.00	Each		
17	Finishing walls with ready mixed Premium acrylic emulsion paint (Company Depot Tinted) having VOC less than 50 gm/litre and UV resistance as per IS 15489:2004, Alkali & fungal resistance, dirt resistance exterior paint of required shade with silicon additives.				
	New work (Two or more coats applied @ 1.43 litre/ 10 sqm over and including priming coat of e	14.10	sqm		
18	Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete				
		9.00	sqm		